




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | |
|---|-----------|---|
| (51) International Patent Classification ⁶ : E05B 73/00, G09F 3/03 | A1 | (11) International Publication Number: WO 97/38193 (43) International Publication Date: 16 October 1997 (16.10.97) |
| (21) International Application Number: PCT/GB97/01004 (22) International Filing Date: 11 April 1997 (11.04.97) (30) Priority Data: 9607553.6 11 April 1996 (11.04.96) GB (71) Applicant (for all designated States except US): SCAFFTAG LIMITED [GB/GB]; Scafftag House, Wimborne Road, Barry, South Glamorgan CF63 3DH (GB). (72) Inventor; and (75) Inventor/Applicant (for US only): MITCHELL, David, Sayers [GB/GB]; "The Barn", Penmark, South Glamorgan CF62 3BP (GB). (74) Agents: LAINE, Simon, James et al.; Wynne-Jones, Laine & James, Morgan Arcade Chambers, 33 St. Mary Street, Cardiff CF1 2AB (GB). | | (81) Designated States: AU, CA, GB, NZ, US, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> |

(54) Title: IMPROVEMENTS RELATING TO SECURITY CONTAINERS**(57) Abstract**

A security container has two dished parts (1, 2) that can be closed together rim (6) to rim (11), irreversibly engaging and making inaccessible a snap fitting (7, 13) within the container. A strop (3) with loops (4) in its ends has those loops placed over part of the snap fitting (13) before closure, leaving its bight (5) outside. The strop (3) is thus made captive when the container is closed. The strop (3) passes through an aperture formed by cutouts (10, 12) in the rims (6, 11).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Latvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | ML | Mali | TR | Turkey |
| BG | Bulgaria | HU | Hungary | MN | Mongolia | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MR | Mauritania | UA | Ukraine |
| BR | Brazil | IL | Israel | MW | Malawi | UG | Uganda |
| BY | Belarus | IS | Iceland | MX | Mexico | US | United States of America |
| CA | Canada | IT | Italy | NE | Niger | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NL | Netherlands | VN | Viet Nam |
| CG | Congo | KE | Kenya | NO | Norway | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NZ | New Zealand | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | PL | Poland | | |
| CM | Cameroon | KR | Republic of Korea | PT | Portugal | | |
| CN | China | KZ | Kazakhstan | RO | Romania | | |
| CU | Cuba | LC | Saint Lucia | RU | Russian Federation | | |
| CZ | Czech Republic | LI | Liechtenstein | SD | Sudan | | |
| DE | Germany | LK | Sri Lanka | SE | Sweden | | |
| DK | Denmark | LR | Liberia | SG | Singapore | | |
| EE | Estonia | | | | | | |

"Improvements relating to Security Containers"

This invention relates to security containers. It is particularly concerned with small containers housing an electronic device which should not be tampered with, and to
5 which physical access is never required. For example, it could be a transponder which may be interrogated from time to time by a radio frequency identification device. There is no need for a lock and key closure: the container should be closable about the device with an irreversible action,
10 requiring damage or even destruction to gain access again.

In addition, the container itself should have means for making it secure to a fixed object associated with or being the member to which the electronic device relates.

It is the aim of this invention to provide such a
15 security container.

According to the present invention there is provided a security container characterised by two parts that snap together in an effectively inseparable manner to make a substantially closed chamber apart from an aperture through
20 which a strop with a closed loop can extend, the container internally having a formation over which the loop can pass with the parts separated, but which is trapped when the parts are snap fitted together.

In the preferred form, the strop has two closed loops,
25 one at each end, whereby both can be passed over the formation to leave the intermediate section as a bight that lies largely outside the container. The aperture is conveniently formed by a cutaway portion in at least one rim

of one part, the opposed rim co-operating as the container is closed to complete the aperture. The aperture may be elongated to accept two passes of the strop, or there may be a separate aperture for each. The strop can thus be passed
5 round an object and its two loops brought together and made captive inside the container whose two parts are then closed together.

Conveniently, the formation is part of the snap fitting. It may be an internally barbed socket on one part
10 which receives and retains a toothed pillar on the other part. The barbs will be inaccessible to manipulation from outside the closed container.

In addition, the container may have externally on at least one part means for retaining a label which will give
15 eye-readable information about the member to which the container is attached.

For a better understanding of the invention, one embodiment will now be described, by way of example, with reference to the accompanying drawings, in which:

20 Figure 1 is a perspective view of a security container,

Figure 2 is an interior plan view of one part of the container,

Figure 3 is a section on the line III-III of Figure 2,

Figure 4 is a section on the line IV-IV of Figure 2,

25 Figure 5 is an interior plan view of another part of the container,

Figure 6 is a section on the line VI-VI of Figure 5,
and

Figure 7 is a section on the line VII-VII of Figure 5.

The container has two complementary circular dish-like parts 1 and 2 with a strop 3, all in plastics material. The strop has loops 4 at each end with an intermediate portion 5 that forms a bight outside the closed container while the loops 4 are trapped inside, as described below.

The part 1 has a stepped rim 6 and a central, rectangular pillar 7 projecting from the centre of its interior surface well above the rim 6. At its upper end, the pillar has teeth 8, on each of the two larger sides, with sloping flanks tapering in towards the top and with undersides substantially at right angles to the pillar. At the base of the pillar there are apertures 9 at each of the larger sides, left by the teeth moulding process. Part of the rim 6 is cut away or reduced at 10.

The other part 2 has a stepped rim 11 complementary to the rim 6, and has a cutaway or reduced portion 12 which will register with the portion 10 when the parts are brought together. The bight 5 of the strop 3 passes through the resultant slot.

While this symmetrical arrangement is preferred, an adequate slot could be obtained by cutting away just one rim. Also, instead of having an elongate slot, two separate apertures, each to take one pass of the strop, could be provided in a similar manner.

The part 2 also has a socket 13 upstanding from the centre of its interior surface to project above the rim 11. Externally it is cylindrical, but internally it is square

Externally it is cylindrical, but internally it is square with barbs 14 pointing back from two opposite sides towards the exterior but with their tips well within the socket. The dimensions are such that, when the two parts 1 and 2 are brought together with the pillar 7 entering the socket 13 and the teeth 8 snapping past the barbs 14, the rims 6 and 11 firmly engage and the top of the pillar 7 is left flush with the exterior of the part 2.

The exterior of the part 2 is different from that of the part 1. It is made flat rather than with a shallow dome and is surrounded by a secondary rim 15 backing the rim 11. At three equidistant positions around this rim 15, lugs 16 project inwardly and provide means for holding a circular label (not shown) which can be worked into the shallow circular recess. The lugs 16 are visible in the interior view of Figure 5 since matching apertures are left beneath them by the moulding process.

Within the part 2, to one side of the socket 13, there are two integrally moulded forks 17 for snap fitting and holding a cylindrical electronic component in the manner of a fuse in an electrical plug. This is just one way in which an item to be protected may be held within the container.

It will be understood that, once the component(s) is (or are) in place, the container is made fast to the associated object by passing the bight 5 of the strop 3 around it as described and then trapping the loops 4 by the socket/pillar assembly as the container is closed.

While the strop with both ends captive within the

container is preferred, it may be appropriate just to have one end so trapped. For example, the strop may be taken round the associated object and one loop passed through the other loop. Then just the one loop would be placed over the
5 socket 13 before the container is closed.

It will be understood that there could be more than just one pillar and socket holding the parts together, and if two were provided, each might receive one loop 4. Further security may also be obtained by having the rims 6,
10 11 snap together in a positive manner.

CLAIMS

1. A security container characterised by two parts (1, 2) that snap together in an effectively inseparable manner to make a substantially closed chamber apart from an aperture (10, 12) through which a strop (3) with a closed loop (4) can extend, the container internally having a formation (13) over which the loop (4) can pass with the parts (1, 2) separated, but which is trapped when the parts are snap fitted together.

2. A security container as claimed in Claim 1, characterised in that the strop (3) has two closed loops (4), one at each end, whereby both can be passed over the formation (13) to leave the intermediate section as a bight (5) that lies largely outside the container.

3. A security container as claimed in Claim 1 or 2, characterised in that the aperture is formed by a cutaway portion (10, 12) in at least one rim (6, 11) of one part, the opposed rim co-operating as the container is closed to complete the aperture.

4. A security container as claimed in Claim 2 and 3, characterised in that the aperture (10, 12) is elongated to accept two passes of the strop (3).


5. A security container as claimed in any of the preceding claims, characterised in that the formation (13) is part of the snap fitting.




6. A security container as claimed in Claim 5, characterised in that the snap fitting includes an internally barbed socket (13) on one part which receives and retains

a toothed pillar (7).

7. A security container as claimed in any preceding claim, characterised in that the container has externally on at least one part (2) means (15, 16) for retaining a label
5 which will give eye-readable information about the member to which the container is attached.

1/3

**Fig. 1**






Fig. 5




Fig. 6




Fig 7

SUBSTITUTE SHEET (RULE 26)

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 97/01004

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 E05B73/00 G09F3/03

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 E05B G09F H05K G08B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|---|-----------------------|
| A | DE 10 95 194 B (THERMO-PLASTIK GMBH) 15 December 1960 see the whole document --- | 1 |
| A | EP 0 594 324 A (SECURITY TAG SYSTEMS INC) 27 April 1994 see the whole document --- | 1 |
| A | FR 796 298 A (LOUIS PRUD'HOMME) 14 December 1936 see the whole document --- | 1 |
| A | CH 656 582 A (SOPLEX SOCIETE DE PERSONNES A) 15 July 1986 see the whole document ----- | 1 |

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

30 July 1997

Date of mailing of the international search report

- 6. 08. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Toussaint, F

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 97/01004

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|---|--|
| DE 1095194 B | | NONE | |
| EP 0594324 A | 27-04-94 | US 5347262 A BR 9304321 A CA 2108219 A DE 69308722 D JP 6325266 A | 13-09-94 26-04-94 24-04-94 17-04-97 25-11-94 |
| FR 796298 A | 03-04-36 | NONE | |
| CH 656582 A | 15-07-86 | BE 895867 A DE 8403776 U LU 85205 A | 10-08-83 30-05-84 26-10-84 |